PORTACOOL APEX 1200™

PACA12001A1

Up to 30°F
Temperature reduction

2,800 sq. ft.
Optimal cooling area

40 ft.
Airflow reach

25 MPH
Air velocity

6,250 CFM
Airflow for faster cooling

51 dB
Noise level

CoolSYNC 2.0
WIFI connectivity

HYDROTEK BY PORTACOOL
Evaporative media

The Utility Player

The Portacool APEX 1200™ is the utility player of the lineup, delivering reliable cooling to mid-sized spaces up to 2,800 square feet. Operating at just 51 dB, it provides powerful airflow with minimal noise—ideal for events, assembly lines, and athletics where focus and productivity matter. A game-changer for open spaces, it tackles heat with a strong 40 ft. stream of cool air, making it the go-to choice when your environment demands consistent, quiet relief from the heat.

AUTOMOTIVE

INDUSTRIAL



OUTDOOR LIVING

SPORTS

CoolSYNC 2.0
Complete Control at Your Fingertips

HYDROTEK BY PORTACOOL
Unparalleled Cooling with Less Maintenance

PORTACOOL PROTECT
Our Industry Leading Warranty

PORTACOOL

Take a closer look

1. **Easy-to-use digital display.** Use the simple onboard controls or unlock all the features of your APEX 1200™ with CoolSync™.
2. **Enhanced fan.** An enhanced fan and motor design offer quieter and more efficient performance.
3. **Built-in handles.** Make portability effortless, allowing you to move your cooler easily across job sites.
4. **HydroTek™ evaporative media.** Portacool's proprietary HydroTek™ media ensures optimal cooling and airflow while keeping costs and maintenance low.
5. **Tough-coat housing.** Built for durability and scratch resistance to withstand the toughest environments.
6. **Recessed hose and power cord.** Keep connections neatly tucked away, ensuring a streamlined look and portability.
7. **Easy water refill.** Swiftly refill the 13-gallon capacity tank via a convenient hatch or through the 3/4" hose connection for uninterrupted cooling experience.
8. **Durable polyolefin wheels.** Designed to withstand heavy use and tough terrain, ensuring smooth mobility.

APEX 1200™ specs

Optimal Cooling Area	2,800 sq. ft.
Air Flow Reach	40 ft.
Air Velocity	25 MPH
Noise Level	51 dB
Speeds	Variable
Fan Blade Size	Centrifugal Fan
Water Reservoir Size	40 Gallons

Airflow	6,250 CFM
Amps	5.0
Electrical Requirements	Standard 120V
Height	58 in.
Width	42 in.
Depth	26 in.
Weight	134 lbs.

PORTACOOL PROTECT

With Portacool Protect™, we stand by every product we make offering comprehensive warranty coverage, including up to 3 years on electrical components and a lifetime warranty on housing.

MADE IN USA

with global and domestic parts