

PORTACOOOL

APEX2000

PACA20001A1



Up to 30°F
Temperature
reduction



4,000 sq. ft.
Optimal cooling
area



60 ft.
Airflow reach



28 MPH
Air velocity



9,000 CFM
Airflow for
faster cooling



58 dB
Noise level



CoolSYNC 2.0
WIFI connectivity



HYDROTEK
BY PORTACOOOL
Evaporative media

The Best of All Worlds

The Portacool APEX 2000™ raises the game for large, active spaces, delivering a balance of size, coverage, and power. Cooling up to 4,000 square feet at only 58 dB, it's ideal for large open garages, manufacturing floors, or outdoor venues where high heat and high activity collide. Its 60 ft. air flow reach creates wide comfort zones that keep teams safe, productive, and focused—without the high cost or noise disruption of fans and traditional cooling systems.

AUTOMOTIVE



INDUSTRIAL



OUTDOOR LIVING



SPORTS



CoolSYNC 2.0

Complete Control at
Your Fingertips

HYDROTEK
BY PORTACOOOL

Unparalleled Cooling with
Less Maintenance



PORTACOOOL
PROTECT

Our Industry Leading
Warranty

PORTACOOOL

Take a closer look



- 1 Easy-to-use digital display.** Use the simple onboard controls or unlock all the features of your APEX 2000™ with CoolSync™.
- 2 Enhanced fan.** An enhanced fan and motor design offer quieter and more efficient performance.
- 3 Built-in handles.** Make portability effortless, allowing you to move your cooler easily across job sites.
- 4 HydroTek™ evaporative media.** Portacool's proprietary HydroTek™ media ensures optimal cooling and airflow while keeping costs and maintenance low.
- 5 Tough-coat housing.** Built for durability and scratch resistance to withstand the toughest environments.
- 6 Recessed hose and power cord.** Keep connections neatly tucked away, ensuring a streamlined look and portability.
- 7 Easy water refill.** Swiftly refill the 13-gallon capacity tank via a convenient hatch or through the 3/4" hose connection for uninterrupted cooling experience.
- 8 Durable polyolefin wheels.** Designed to withstand heavy use and tough terrain, ensuring smooth mobility.

APEX 2000™ specs

Optimal Cooling Area	4,000 sq. ft.
Air Flow Reach	60 ft.
Air Velocity	28 MPH
Noise Level	58 dB
Speeds	Variable
Fan Blade Size	Centrifugal Fan
Water Reservoir Size	45 Gallons

Airflow	9,000 CFM
Amps	8.0
Electrical Requirements	Standard 120V
Height	68 in.
Width	54 in.
Depth	30 in.
Weight	191 lbs.



With Portacool Protect™, we stand by every product we make offering comprehensive warranty coverage, including up to 3 years on electrical components and a lifetime warranty on housing.

