



PORTACOO[®] APEX4000[™]

PACA40001A1



Up to 30°F
Temperature
reduction



6,000 sq. ft.
Optimal cooling
area



50 ft.
Airflow reach



25 MPH
Air velocity



13,350 CFM
Airflow for faster
cooling



62 dB
Noise level



CoolSYNC 2.0
WIFI connectivity



HYDROTEK[®]
BY PORTACOO[®]
Evaporative media

Large and in Charge

The Portacool APEX 4000[™] is large and in charge— built to dominate heat in spaces up to 4,000 square feet. Despite its size, it runs at a modest 62 dB, making it a workhorse for industrial settings, event venues, and covered outdoor areas where expansive airflow is a must. With a 50 ft. cooling reach, this powerhouse provides steady relief across wide open zones, ensuring comfort and compliance without sacrificing energy efficiency.

AUTOMOTIVE



INDUSTRIAL



OUTDOOR LIVING



SPORTS



CoolSYNC 2.0

Complete Control at
Your Fingertips

HYDROTEK[®]
BY PORTACOO[®]

Unparalleled Cooling with
Less Maintenance



PORTACOO[®]
PROTECT

Our Industry Leading
Warranty

PORTACOO[®]

Take a closer look



- 1 Easy-to-use digital display.** Use the simple onboard controls or unlock all the features of your APEX 4000™ with CoolSync™.
- 2 Enhanced fan.** An enhanced fan and motor design offer quieter and more efficient performance.
- 3 Built-in handles.** Make portability effortless, allowing you to move your cooler easily across job sites.
- 4 HydroTek™ evaporative media.** Portacool's proprietary HydroTek™ media ensures optimal cooling and airflow while keeping costs and maintenance low.
- 5 Tough-coat housing.** Built for durability and scratch resistance to withstand the toughest environments.
- 6 Recessed hose and power cord.** Keep connections neatly tucked away, ensuring a streamlined look and portability.
- 7 Easy water refill.** Swiftly refill the 13-gallon capacity tank via a convenient hatch or through the 3/4" hose connection for uninterrupted cooling experience.
- 8 Durable polyolefin wheels.** Designed to withstand heavy use and tough terrain, ensuring smooth mobility.

APEX 4000™ specs

Optimal Cooling Area	6,000 sq. ft.
Air Flow Reach	50 ft.
Air Velocity	25 MPH
Noise Level	62 dB
Speeds	Variable
Fan Blade Size	Centrifugal Fan
Water Reservoir Size	55 Gallons

Airflow	13,350 CFM
Amps	9.0
Electrical Requirements	Standard 120V
Height	77 in.
Width	63 in.
Depth	33 in.
Weight	220 lbs.



With Portacool Protect™, we stand by every product we make offering comprehensive warranty coverage, including up to 3 years on electrical components and a lifetime warranty on housing.

