PORTACOOL

APEX 6500™

PACA65001A1

Up to 30°F
Temperature reduction

8,500 sq. ft.
Optimal cooling area

40 ft.
Airflow reach

24 MPH
Air velocity

25,000 CFM
Airflow for faster cooling

68 dB
Noise level

CoolSYNC 2.0
WIFI connectivity

HYDROTEK by PORTACOOL
Evaporative media

Extreme Cooling for Large Spaces

Designed to dominate, the Portacool APEX 6500™ delivers extreme cooling for large spaces. Easily covering up to 8,500 square feet with a commanding 40 ft. air reach, and 68 dB level—about as loud as a high-capacity home air conditioner. It's designed for the toughest industrial and commercial environments—distribution centers, manufacturing spaces, and construction sites. The APEX 6500, the heavyweight of cooling solutions, conquers the heat without breaking the bank.

AUTOMOTIVE

INDUSTRIAL

OUTDOOR LIVING

SPORTS



CoolSYNC 2.0™
Complete Control at Your Fingertips

HYDROTEK BY PORTACOOL
Unparalleled Cooling with Less Maintenance

PORTACOOL PROTECT
Our Industry Leading Warranty

Take a closer look

1. **Easy-to-use digital display.** Use the simple onboard controls or unlock all the features of your APEX 6500™ with CoolSync™.
2. **Enhanced fan.** An enhanced fan and motor design offer quieter and more efficient performance.
3. **Built-in handles.** Make portability effortless, allowing you to move your cooler reasily across job sites.
4. **HydroTek™ evaporative media.** Portacool's proprietary HydroTek™ media ensures optimal cooling and airflow while keeping costs and maintenance low.
5. **Tough-coat housing.** Built for durability and scratch resistance to withstand the toughest environments.
6. **Recessed hose and power cord.** Keep connections neatly tucked away, ensuring a streamlined look and portability.
7. **Easy water refill.** Swiftly refill the 13-gallon capacity tank via a convenient hatch or through the 3/4" hose connection for uninterrupted cooling experience.
8. **Durable polyolefin wheels.** Designed to withstand heavy use and tough terrain, ensuring smooth mobility.

APEX 6500™ specs

Optimal Cooling Area	8,500 sq. ft.
Air Flow Reach	40 ft.
Air Velocity	24 MPH
Noise Level	68 dB
Speeds	Variable
Fan Blade Size	Centrifugal Fan
Water Reservoir Size	66 Gallons

Airflow	25,000 CFM
Amps	14.7
Electrical Requirements	Standard 120V
Height	90 in.
Width	78 in.
Depth	39 in.
Weight	290 lbs.

PORTACOOL PROTECT

With Portacool Protect™, we stand by every product we make offering comprehensive warranty coverage, including up to 3 years on electrical components and a lifetime warranty on housing.

MADE IN USA

with global and domestic parts